

CRUX LED1X1500 E308 T840 OP • 1019662



Product:	Crux LED1x1500 E308 T840 OP		
Order code:	1019662		
Family:	Crux LED		
Product group:	Downlights		


GENERAL DATA

Description:	Recessed mounted LED downlight Light distribution type: direct		
	Optical system: opal polycarbonate diffuser Housing: aluminium		
	Colour: white (RAL9016)		
Instalation:	In ceilings with cut-out openings (mounting brackets included). Screw terminal, 2x1x1.5mm2		
Environment	Indoor		
Application	office, education, corridor, retail, public place, showroom, hotel, bathroom		


ELECTRICAL DATA

Mains voltage:	220-240V, 0/50/60Hz	System power*, W:	13.1
Power factor:	>0,95	Control gear:	ECG on/off
Integrated sensor:	None	Connection:	Push-in terminal, 2x1.5mm2
LIGHTING DATA			
Light source and cap, W:	LED	Light source included:	yes
Luminaire output*, lm(ta+25°C):	1479	System efficacy, lm/W:	113
CRI (Ra):	80+	сст, к:	4000
SDCM:	3	Light Distribution:	Symmetrical wide beam (76125)
Distribution Type:	Direct	Beam angle, °:	96
UGR index:	≤22	LED lifetime, h:	100000/L80B50
TECHNICAL DATA			
Net weight, kg:	0.8	Mounting holes/cut-out dimensions, mm:	d185
Quantity in package, pcs:	1	Packaging volume, m3/pcs:	0.0046
Pallet quantity, pcs:	190		
Dimensions, mm:	200x200x90		
STANDARDS			
Operating temperature range, °C:	ta 0+35	Protection class IEC:	II
Ingress protection code:	IP44	Mechanical impact resistance:	IK04
EEC:	E	Certificates:	CE, RoHS
Warranty:	3 years		

Technical drawing (.jpg)



Light distribution curve (.jpg)



Note:

Tolerance range for optical and electrical data: $\pm 10\%$. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

Date of issue: 2023-07-10 ■ NORTHCLIFFE LIGHTING, UAB ■ Raudondvario pl. 101, LT-47184 Kaunas, Lithuania ■ info@northcliffe.org ■ www.northcliffe.org