

## SLC NEON FULL FLEX 4000K 9W 450LM 1-5M IP67

### SM16003

## **Product description**

Neon Flex is an LED strip encapsulated in high-quality silicone that opens up new applications. Can be bent and twisted in all directions. IP67 for outdoor installation. Applications: both indoors and outdoors as decorative lighting, garden lighting, accent lighting and more. Sold to measure. When ordering, state the desired number of meters. Remember to select the connection. The connector is delivered fully assembled on the strip with an end piece at the opposite end.

Can be bent sideways, up and down and twisted in all directions

Available in lengths up to 5 meters

Free-cut

IP67 for outdoor installation

Applications: both indoor and outdoor such as decor lighting, garden lighting, effect lighting and more Sold in custom lengths. When ordering, specify the desired number of meters.

**Technical data** 

Model	Hose
Lamp type	LED not exchangeable
Lamp power per meter	9 Watt
Luminaire efficacy	50 Lumen/Watt
Lamp voltage	24 - 24 Volt
Type of control gear	LED operating device voltage-controlled
Exchangeable control gear	Yes
Lumen maintenance at median useful life of	96 Percentage
Degree of protection (IP)	IP67
Max. system power	45 Watt

Mounting method	Surface mounting/recessed mounting
Number of nodes per meter	120
Luminous flux per meter	450 Lumen
Voltage type	DC
Beam angle	120 Degrees
Suitable for dimmer	Yes
Energy efficiency class of the light source a	F
Failure rate at median useful life of 50,000 h	10 Percentage
Protection class	Ш
Colour of light	White

03/06/2024







#### THE LIGHT GROUP GmbH Am Schafbrinke 62 | 30519 Hannover | Germany Tel.: +49 (0)511 - 807 486 10 | E-Mail: info@tlg.no

THE LIGHT GROUP AS Sagmyra 2A, 4624 | Kristiansand S | Norway Tel.: +47 38 00 21 01 | E-Mail : post@tlg.no






# The Light Group Datasheet



Colour temperature	4000 - 4000 Kelvin
Colour of light adjustable	No
Width	20 Millimetre
Length	1 Millimetre
With connection set	Yes
Type of wiring	Ending
LED-Strip length (m)	1
Operating temperature (Ta)	-25°C ~ +35°C
Produced by	The Light Group

Colour rendering index CRI	80-89
Luminous flux adjustable	Continuously variable
Height/depth	19,5 Millimetre
With end piece	Yes
With protective cover	Yes
Number of poles	2
Color	White
Brand	SLC






THE LIGHT GROUP GmbH Am Schafbrinke 62 | 30519 Hannover | Germany Tel.: +49 (0)511 - 807 486 10 | E-Mail: info@tlg.no

THE LIGHT GROUP AS Sagmyra 2A, 4624 | Kristiansand S | Norway Tel.: +47 38 00 21 01 | E-Mail : post@tlg.no



## The Light Group Datasheet



Scandinavian Lighting Concept



THE LIGHT GROUP GmbH Am Schafbrinke 62 | 30519 Hannover | Germany Tel.: +49 (0)511 - 807 486 10 | E-Mail: info@tlg.no

THE LIGHT GROUP AS Sagmyra 2A, 4624 | Kristiansand S | Norway Tel.: +47 38 00 21 01 | E-Mail : post@tlg.no